



**KWC**

KWC  
**PILLAR TAP**

## KWC PILLAR TAP

Not only in its ergonomics and user-friendliness, but also in its use of resources, less is more – 5 liters/minute, to be specific. The KWC pillar tap is suitable for hot and cold water connections and, due to its sleek design, is an aesthetic fit in any setting.

At home, too, the KWC pillar tap is the ideal solution. It works well as a space-saving and resource-saving washbasin faucet or as a dispenser for drinking water.



### Pillar tap

- Efficiency class A
- Operating handle integrated into the spout
- Fixed spout
  - Neoperl® Caché®
- Ceramic disc valve ½" 90°
- Connecting thread ½"
- Mounting hole size ø22mm or ø35mm

#### 25.001.010.000

chromeline

A 120, G ½"

Flow rate 4 l/min (3 bar)



### Pillar tap

- Efficiency class A
- Operating handle integrated into the spout
- Fixed spout
  - Neoperl® Caché®
- Ceramic disc valve ½" 90°
- Connecting thread ½"
- Mounting hole size ø22mm or ø35mm

#### 25.001.011.751

industrial black

A 125, G ½"

Flow rate 5 l/min (3 bar)



### Pillar tap

- Efficiency class A
- Operating handle integrated into the spout
- Fixed spout
  - Neoperl® Caché®
- Ceramic disc valve ½" 90°
- Connecting thread ½"
- Mounting hole size ø22mm or ø35mm

#### 25.001.011.700

stainless steel

A 125, G ½"

Flow rate 5 l/min (3 bar)